an assembly housed in the unitary housing and comprising a nonconductive housing and power and ground conductors, the power and ground conductors coupled to the cable;

a circuit board coupled to the assembly;

a plurality of contacts coupled to the circuit board;

a magnetic attraction plate positioned around the plurality of contacts, the attraction plate and the plurality of contacts protruding through a second opening in the unitary housing in a second direction, the second direction orthogonal to the first direction;

a first light-emitting diode coupled to the circuit board;

a first light pipe over the first light-emitting diode; and

a first light insulator around the first light-emitting diode and the first light pipe, the first light insulator to limit stray illumination and to allow illumination through a third opening in the unitary housing.

17. The cable plug of claim **16** further comprising a second light pipe in the third opening in the unitary housing.

18. The cable plug of claim **17** wherein the second light pipe is formed using an adhesive.

19. The cable plug of claim **16** further comprising:

a second light-emitting diode on the circuit board;

a second light pipe over the second light-emitting diode; and

a second light insulator around the second light-emitting diode and the second light pipe, the second light insulator to limit stray illumination and to allow illumination through a fourth opening in the unitary housing.

20. The cable plug of claim **16** wherein the unitary housing is formed of aluminum.

21. The cable plug of claim **16** wherein the circuit board is a flexible circuit board.

22. The cable plug of claim **16** wherein the first light insulator is formed using foam.

23. The cable plug of claim **16** wherein the unitary housing and the attraction plate form an enclosure that encloses the assembly, the circuit board, the plurality of contacts, the first light-emitting diode, and the first light insulator.

* * * * *